

# "High Frequency Ceramic Solutions"

## 2.4 GHz WLAN, Home RF, Bluetooth, 802.11 b/g, Antenna P/N 2450AT43B100 With Ground Clearance Requirements Minimized

Detail Specification: 11/14/2016

Page 1 of 5

**Tip: This antenna "loves" to be mounted on PCB corners for optimum performance**

### General Specifications

<b>Part Number</b>	2450AT43B100	<b>Input Power</b>	2W max. (CW)
<b>Frequency Range</b>	2400 - 2500 Mhz	<b>Reel Quantity</b>	1,000
<b>Peak Gain</b>	1.3 dBi typ. (XZ-V)	<b>Operating Temperature</b>	-40 to +105°C
<b>Average Gain</b>	-0.5 dBi typ. (XZ-V)	<b>Storage Temperature</b>	-40 to +105°C
<b>Return Loss</b>	9.5 dB min.	<b>Recommended Storage Conditions (for unused product on T&amp;R)</b>	+5 to +35°C, Humidity: 45-75%RH, 18 months max.
<b>Radiation Pattern</b>	Omnidirectional		


Would you like us to tune the antenna to your PCB? Contact us at:  
[www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

### Part Number Explanation

<b>P/N Suffix</b>	<b>Packaging Style</b>	Bulk	Suffix = S	Eg. 2450AT43B100S
		T & R	Suffix = E	Eg. 2450AT43B100E
	<b>Termination Style</b>	100% Tin	Suffix = None	Eg. 2450AT43B100(E or S)
	<b>Evalutation Board</b>	2450AT43B100-EB1SMA (comes pre-tuned with SMA connector)		

### Mechanical Dimensions


	In	mm
<b>L</b>	0.276 ± 0.008	7.00 ± 0.20
<b>W</b>	0.079 ± 0.008	2.00 ± 0.20
<b>L1</b>	0.102 ± 0.008	2.60 ± 0.20
<b>W1</b>	0.020 ± 0.008	0.50 ± 0.20
<b>T</b>	0.079 +.004/-0.008	2.00 +0.1/-0.2
<b>a</b>	0.020 ± 0.012	0.50 ± 0.30



Want the layout file? Request it at:  
[www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

### Terminal Configuration

No.	Function
1	Feed Point
2	NC
3	NC
4	NC



NOTE: Pins 2, 3 & 4, although "NC", must be soldered to their corresponding PCB pads for proper electrical operation



Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.

# "High Frequency Ceramic Solutions"

2.4 GHz WLAN, Home RF, Bluetooth, 802.11 b/g, Antenna

P/N 2450AT43B100

With Ground Clearance Requirements Minimized

Page 2 of 5

Detail Specification: 11/14/2016


## Mounting and Layout Guidelines:

Mount these devices with red mark facing up. Units: mm

**Need help designing the antenna in? Use our antenna design services!**

[www.johansontechnology.com/ipc-antenna-services](http://www.johansontechnology.com/ipc-antenna-services)

**We provide 2 Free layout reviews and if you need us to tune and characterize the antenna on your design (anechoic chamber) we can do that too (lab fee may apply for the latter).**



**IMPORTANT!** Matching circuit and component values will be different on your PCB, this will depend on PCB layout and shape, encasement, etc

\*Antenna feed line width should be designed to provide 50  $\Omega$  impedance otherwise improper operation

**Note 1:** Pins 2, 3 & 4, although "NC", must be soldered to their corresponding PCB pads for proper operation

**Note 2:** It is recommended that the designer leave available slots for a "pi" (or shunt-series-shunt) network. The antenna matching network values above are used when antenna is mounted on Johanson's evaluation board. The matching values on client's PCB will be different. Go to: [www.johansontechnology.com/tuning](http://www.johansontechnology.com/tuning) and see how to obtain the new values. If you need need us to tune it for you or would like the layout files, please contact our RF Applications Eng Team at: [www.johansontechnology.com/ask-a-question](http://www.johansontechnology.com/ask-a-question)

Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



2016 Johanson Technology, Inc. All Rights Reserved

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.1

2016 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"

2.4 GHz WLAN, Home RF, Bluetooth, 802.11 b/g, Antenna

P/N 2450AT43B100

With Ground Clearance Requirements Minimized


Page 3 of 5

Detail Specification: 11/14/2016

## EVB used to characterize the antenna


Would you like to order this pre-tuned EVB? Click on:

[www.johansontechnology.com/request-a-sample](http://www.johansontechnology.com/request-a-sample) and please reference p/n: 2450AT43B100-EB1SMA  
(comes with SMA connector)



## Typical Electrical Characteristics (T=25°C)

With Proper Matching Circuit



Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



2016 Johanson Technology, Inc. All Rights Reserved

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.1

2016 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"

2.4 GHz WLAN, Home RF, Bluetooth, 802.11 b/g, Antenna


P/N 2450AT43B100

With Ground Clearance Requirements Minimized

Page 4 of 5

Detail Specification: 11/14/2016

## Typical Electrical Characteristics/Radiation Patterns (T=25°C)



Johanson Technology, Inc. reserves the right to make design changes without notice.  
All sales are subject to Johanson Technology, Inc. terms and conditions.



2016 Johanson Technology, Inc. All Rights Reserved

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.1

2016 Johanson Technology, Inc. All Rights Reserved

# "High Frequency Ceramic Solutions"

2.4 GHz WLAN, Home RF, Bluetooth, 802.11 b/g, Antenna  
With Ground Clearance Requirements Minimized

P/N 2450AT43B100

Detail Specification: 11/14/2016

Page 5 of 5

###

## Antenna layout review, tuning, and characterization services

[www.johansontechnology.com/ipc-antenna-services](http://www.johansontechnology.com/ipc-antenna-services)

## More SMD Chip Antennas at:

[www.johansontechnology.com/antennas](http://www.johansontechnology.com/antennas)

## Soldering Information

[www.johansontechnology.com/ipcsoldering-profile](http://www.johansontechnology.com/ipcsoldering-profile)

## Antenna layout and tuning techniques (How to obtain the new antenna matching values)

[www.johansontechnology.com/tuning](http://www.johansontechnology.com/tuning)

## Packaging information

<http://www.johansontechnology.com/tape-reel-packaging>

## RoHS2 (6/6) full compliance

[www.johansontechnology.com/rohs-compliance](http://www.johansontechnology.com/rohs-compliance)

## MSL Info

[www.johansontechnology.com/msl-rating](http://www.johansontechnology.com/msl-rating)

## P/N Explanation and Breakdown

[www.johansontechnology.com/ipc-pn-explained](http://www.johansontechnology.com/ipc-pn-explained)

Recommended Storage Conditions of  
uninstalled product still on T&R

-40 ~ +85 °C, Humidity 45~75%RH, 18 mos. Max

Johanson Technology, Inc. reserves the right to make design changes without notice. Please confirm the specifications and delivery conditions when placing your order. All sales are subject to Johanson Technology, Inc. terms and conditions.

Technical Author: Manuel Carmona



[www.johansontechnology.com](http://www.johansontechnology.com)

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

Ver 2.1

2016 Johanson Technology, Inc. All Rights Reserved